

TITAN BRUTE SHIELDS



The name means what it says, Built tough for keeping the job moving in the roughest conditions, it's a BRUTE.

How Kundel's trench shields compare to others

Common features

- P.E. Certified
- O.S.H.A. Compliant
- Tabulated Data
- 1/2" x 3" Cutting Bar

Kundel goes beyond...

- Formed Steel Design
- Continuous Steel Members
- 18" High Tapered Knife Edge
- Internal Pounding Members
- Reinforced Knife Edge
- Internal Stacking System
- Easy Slide Outside Edge
- One C Soil Depth Rating
- Vertical Reinforced Pounding Area
- Reinforced Through Wall Sockets

Your Local Trench Protection Specialist:

IMPORTANT: Kundel believes that every Contractor has individual concerns that must be addressed individually, not generically. Kundel uses its years of in-the-trench experience, as well as in-depth knowledge of O.S.H.A. regulations, to custom fit you with a shoring or shielding system that will increase your production and profits, while working within O.S.H.A. guidelines, please call...

Titan Brute 3

3 1/2" Side Walls
Production Depth 10' to 24'

Featuring:

- 18" Knife Edge Taper
- 7" (X) Strong Pipe Sockets
- 1" Thick Pounding Pads
- 2 1/2" Solid Stacking Lug Bar
- 1/2" x 3" Cutting Bar

Length	4'			5'			6'			8'			10'		
	Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.	
16' - ST	4525	30K	16' - K	4786	32K	16' - K	5638	38K	16' - K	7132	48K	16' - K	8715	58K	
18' - ST	4784	32K	18' - K	5210	35K	18' - K	6162	41K	18' - K	7815	52K	18' - K	9541	64K	
20' - ST	5259	35K	20' - K	5665	38K	20' - K	6718	45K	20' - K	8530	57K	20' - K	10353	69K	
22' - ST	5686	38K	22' - K	6103	41K	22' - K	7313	49K	22' - K	9161	61K	22' - K	11143	74K	
24' - ST	6142	41K	24' - K	6537	44K	24' - K	7753	52K	24' - K	9855	66K	24' - K	11981	80K	
26' - ST	6531	44K	26' - K	6926	46K	26' - K	8212	55K	26' - K	10436	70K	26' - K	12675	85K	

Titan Brute 5

5" Side Walls
Production Depth 16' to 28'

Featuring:

- 18" Knife Edge Taper
- 7" (X) Strong Pipe Sockets
- 1 1/2" Thick Pounding Pads
- 2 1/2" Solid Stacking Lug Bar
- 1/2" x 3" Cutting Bar

Length	4'			5'			6'			8'			10'		
	Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.	
16' - ST	4750	32K	16' - K	5174	34K	16' - K	6437	43K	16' - K	7757	52K	16' - K	9295	62K	
18' - ST	5179	35K	18' - K	5937	40K	18' - K	7021	47K	18' - K	8870	59K	18' - K	10992	73K	
20' - ST	5644	38K	20' - K	6459	43K	20' - K	7660	51K	20' - K	9930	66K	20' - K	11996	80K	
22' - ST	6113	41K	22' - K	6991	47K	22' - K	8283	55K	22' - K	10695	71K	22' - K	12927	86K	
24' - ST	6543	44K	24' - K	7477	50K	24' - K	8887	59K	24' - K	11476	77K	24' - K	13856	92K	
26' - ST	6974	46K	26' - K	7958	53K	26' - K	9470	63K	26' - K	12192	81K	26' - K	14725	98K	

Titan Brute 6

6 3/4" Side Walls
Production Depth 18' to 34'

Featuring:

- 18" Knife Edge Taper
- 6" (2X) Strong Pipe Sockets
- 1 1/2" Thick Pounding Pads
- 3" Solid Stacking Lug Bar
- 1/2" x 3" Cutting Bar

Length	4'			5'			6'			8'			10'		
	Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.	
16' - ST	5626	38K	16' - K	6124	41K	16' - K	7146	48K	16' - K	8956	60K	16' - K	10690	71K	
18' - ST	6282	42K	18' - K	6834	46K	18' - K	7987	53K	18' - K	9982	67K	18' - K	11898	79K	
20' - ST	6552	44K	20' - K	7164	48K	20' - K	8444	56K	20' - K	10629	71K	20' - K	12698	85K	
22' - ST	7043	47K	22' - K	7691	51K	22' - K	9071	60K	22' - K	11394	76K	22' - K	13623	91K	
24' - ST	7497	50K	24' - K	8191	55K	24' - K	9712	65K	24' - K	12230	82K	24' - K	14623	97K	
26' - ST	7949	53K	26' - K	8720	58K	26' - K	10300	69K	26' - K	12958	86K	26' - K	15484	103K	

Titan Brute 8

8 1/2" Side Walls
Production Depth 20' to 42'

Featuring:

- 18" Knife Edge Taper
- 6" (2X) Strong Pipe Sockets
- 1 1/2" Thick Pounding Pads
- 3" Solid Stacking Lug Bar
- 1/2" x 3" Cutting Bar

Length	4'			5'			6'			8'			10'		
	Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.	
16' - ST	6630	44K	16' - K	6670	44K	16' - K	7893	53K	16' - K	9951	66K	16' - K	12127	81K	
18' - ST	7488	50K	18' - K	7486	50K	18' - K	8878	59K	18' - K	11191	75K	18' - K	13580	91K	
20' - ST	7953	53K	20' - K	7797	52K	20' - K	9293	62K	20' - K	11773	78K	20' - K	14322	95K	
22' - ST	8491	57K	22' - K	8393	56K	22' - K	9996	67K	22' - K	12682	85K	22' - K	15387	103K	
24' - ST	9119	61K	24' - K	8955	60K	24' - K	10721	71K	24' - K	13579	91K	24' - K	16471	110K	
26' - ST	9771	65K	26' - K	9576	64K	26' - K	11455	76K	26' - K	14496	97K	26' - K	17552	117K	

Titan Brute 9

9 1/2" Side Walls
Production Depth 20' to 50'

Featuring:

- 18" Knife Edge Taper
- 6" (2X) Strong Pipe Sockets
- 1 1/2" Thick Pounding Pads
- 3" Solid Stacking Lug Bar
- 1/2" x 3" Cutting Bar

Length	4'			5'			6'			8'			10'		
	Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.		Shield Wt.	Mach Wt.	
20' - ST	8249	55K	20' - K	8355	56K	20' - K	9996	67K	20' - K	12670	84K	20' - K	15092	101K	
22' - ST	8929	60K	22' - K	8992	60K	22' - K	10772	72K	22' - K	13630	91K	22' - K	16198	108K	
24' - ST	9583	64K	24' - K	9581	64K	24' - K	11520	77K	24' - K	14589	97K	24' - K	17353	116K	
26' - ST	10275	69K	26' - K	10235	68K	26' - K	12299	82K	26' - K	15564	104K	26' - K	18486	123K	
28' - ST	10967	73K	28' - K	10889	73K	28' - K	13078	87K	28' - K	16539	110K	28' - K	19619	131K	
30' - ST	11659	78K	30' - K	11543	77K	30' - K	13857	92K	30' - K	17514	117K	30' - K	20752	138K	

LARGER 28'+ AND CUSTOM SHIELDS ARE AVAILABLE (Spreaders sold separately)